

### DESCRIPTION

The PSP Corium Welder 34-435 is a TIG welding glove of A-grade grain leather with a thickness of 1,0 - 1,2 mm with a split leather cuff of 1,0 - 1,2 mm thickness with a cuff length of 15 cm.





This glove has a total length of 35 cm. The critical seams have been strengthened paspoil. The glove has a cow leather wrist reinforcement and is unlined. The glove is free of Chromium VI and PCP.

The PSP Corium Welder 34-435 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN standards: EN420 / EN388:2016 / EN407 and EN 12477 type B.

### CHARACTERISTICS

- ▲ Cow grain leather palm and back, thickness 1,0 - 1,2 mm
- ▲ 15 Cm split leather cuff
- ▲ Total length 35 cm
- ▲ Free of Chromium VI and PCP
- ▲ Certified according to EN420 / EN388:2016 / EN407 and EN12477 Type B

### CERTIFICATIONS

 CAT II	 EN 388:2016 4144X	Abrasion resistance = 4 Cut resistance = 1 Tear resistance = 4 Puncture resistance = 4 Cut ISO 13997 = X	 EN 407 413142	 EN 12477 Type B
--	---	--	---	---

### APPLICATIONS

TIG Welding jobs | Industry | Metal industry | General work



### PRODUCT INFORMATION

<b>Material</b>	Palm and back: Cow grain leather Cuff: Cow split leather
<b>Color</b>	Natural
<b>Lining</b>	-
<b>Length (mm)</b>	350
<b>Cuff (mm)</b>	150

### ORDER DETAILS

Size	Item number	Packing unit
10 / XL	2.03.34.435.10	10 x 12 (120 pairs)

CUT ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable

