

# TECHNICAL SPECIFICATION



## EVOGuard®M Forestry Browguard Systems

EVOGuard®M3 Forestry Browguard System / ADB28A-400-800



### DESCRIPTION

The EVOGuard® M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

### OPTIONS

EVOGuard®M2 Forestry Browguard System  
(ADB28A-300-800)

**EVOGuard®M3 Forestry Browguard System  
(ADB28A-400-800)**

### SAFETY STANDARDS

EN 1731 • EN 352-3 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.


Page 1 of 3 / Issued 17 Mar 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

	Harness 6 Point Multi-Position Adjustment/Fitting System		Universal Accessories Slot Yes
	Wheel Ratchet Yes		Integrated Eyewear Fitted
	Manufacturer's Trademark JSP Dagger		Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s <sup>2</sup> Maximum protection for glasses F
	Visible Light Transmittance (VLT) 80%		Visor Length 18cm
	Mounting Browguard/Helmet		SNR 31 dB
	Adjustable Yes		BSI Kitemark Yes
	JSPCheck Yes		Material 30% Glass Filled Nylon Browguard
	Material ABS Frame and Chemically Etched Stainless Steel Mesh		Material ABS/Stainless Steel Wire
	Recyclable Yes		Product Weight 605g

## FEATURES



### Visor Range

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



### Dual Layer Protection

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



### Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



### Supreme Comfort & Fit

Features the new JSP Revolution® wheel ratchet, securely tightening and holding the unit firmly in position, no matter the task or amount of user movement involved. System comes complete with a wraparound, soft foam backed, replaceable, Chamlon™ sweatband offers superior comfort.



### Balanced & Secure

Fitted to a browguard or helmet, the self-lubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



### Product Compatibility

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™ disposable masks and the Sonis® helmet mounted ear defender range.



### Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.



### Maximum Adjustability

Multiple fitting positions allow the wearer to adjust the browguard in three ways. An over the crown slide fitting combined with a forward and back adjustment, maximises compatibility with different head shapes.

JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.


Page 2 of 3 / Issued 17 Mar 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.






### High Quality Materials

The EVOGuard®M3 Forestry Visor is comprised of an ABS over-moulded frame with an etched stainless steel visor material.



### Visible Light Transmittance

The EVOGuard®M3 Forestry Visor offers 80% visible light transmittance.



### Impact Protection

The EVOGuard®M3 Forestry Visor features an F - Impact rating, offering increased impact resistance when fitted to a EVOGuard®M Forestry browguard or helmet unit.

## RANGE

## DOWNLOADS



[Image Pack \(ZIP\)](#)

[doc-evoguard.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 17 Mar 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

