

TECHNICAL DATASHEET

REV.00

619020100



FEATURES:

- Linear and compact design
- Can be worn over any prescription spectacles thanks to its spherical lens
- Version unvented or provided with indirect ventilation system
- Wide, fully adjustable headband

FEATURES FRAME:

Frame Typology	Mask
PPE field of view	>40°
Complete PPE weight (g)	84
Size (mm)	155
Frame Features	PVC
Elastic Band Features	Elastic tissue
Ventilation System	Indirect Ventilation

FEATURES OCULARS/LENSES:

VLT% (+/-5%)	91.2
Material Ocular/Flip-up	Polycarbonate
Colour	Clear
Technical Treatment	Antiscratch PLUS Antifog PLUS
Thickness [mm](+/- 0.1)	2.25
Curvature	Spheric
Optical Class	1
UV Protection	380 nm
Spare parts	-

MARKS:

Standard Reference	EN166 EN170
Frame Marking	U EN166 3 4 9 B 2C-1.2 CE
Ocular/Flip-up Marking	2C-1.2 U 1 B 9 K N CE

FIELDS OF EMPLOYMENT

Protection against droplets and splashes of liquids (3); Protection against high-speed particles 120 m/s - medium energy (B); Protection against large dust particles (>0.5 µm) (4); Protection against molten metals and hot solids (9); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

